

CHE 2-28 R SDS-plus

Universal rotary hammer drill, 2,5 kg, SDS-plus

Order no. 461490

GTIN 4030293205611



- + Light 800 watt hammer drill and chisel hammer, pistol-shaped with the clockwise/anticlockwise rotation function
- + Hammer drilling
- + Max. drilling range up to 28 mm in concrete
- + Ideal for drilling and hammer drilling, diameters from 4-18 mm in masonry and concrete for dowel fixings or through-holes.
- + For light-duty chiselling work when removing plaster and tiles
- + Quick tool change: universal application, with SDS Plus drill chuck or 13 mm quick-release chuck
- + Drilling chuck can be removed without tools
- + Clockwise/anti-clockwise rotation with switchover via carbon brush reverser. As a result, almost identical torque in both directions of rotation
- + Depth limit gauge: for precision drilling
- + Rotation stop for chiselling
- + Accelerator switch with lock-on function



Technical data

Power consumption	800 W
Voltage	230 V
Frequency	50/60 Hz
Tool holder, drill and chisel	SDS-plus
Max. single impact energy	2.7 J
No-load speed	0 - 1300 rpm
No-load blows	0 - 4000 1 rpm
Chuck clamping width	1,5 - 13 mm
Max. drilling diameter in concrete	28 mm
Max. drilling diameter in wood	30 mm
Max. drilling diameter in steel	13 mm
Cable length	4.0 m
Dimensions WxLxH	390 x 83 x 205 mm
Weight	2.8 kg

Standard equipment

- 1 Chuck (468843)
- 1 Handle (417661)
- 1 Depth stop (417769)
- 1 Carrying case L-BOXX® (414085)
- 1 Case insert (469033)