

# MXE 1000 + HP2 120

1010 watt 1-speed mixer with accelerator trigger switch

Order no. 495883

GTIN 4030293224445

- + Large, rugged single-speed gear unit with optimum gear ratio for high torque
- + Full-wave electronic control: with soft start, temperature monitoring, overload protection and accelerator switch - for a controlled run-up to the optimum mixing speed. Sustained power in all speed ranges
- + On/off switch with lock and protection at power interruption. Ideal for stationary operation in a mixing station
- + The flexible rubber sleeve over the on/off switch prevents the ingress of dirt. No malfunctions caused by jammed switches
- + Ergonomic handles on the drive unit: low weight, fatigue-free arm posture and upright body posture allow comfortable, ergonomic operation
- + Four corner guards with rubber buffer provide secure storage during transportation and offer protection against shocks and impacts at the building site
- + Protective cap above the motor housing guides the cooling air flow and prevents the ingress of splashing water
- + For mixed applications up to 40 kg
- + Proven standard mixer is ideal for users operating mainly in the low speed range
- + With mixing paddle WR2 for mixture: pasty to tough. Tile adhesive, grout, filler compound, adhesive, finished plaster, adhesive mortar, ...



## Technical data

|                             |                    |
|-----------------------------|--------------------|
| Power consumption           | 1010 W             |
| Power output                | 550 W              |
| Voltage                     | 230 V              |
| Frequency                   | 50/60 Hz           |
| Max. mixing basket diameter | 120 mm             |
| Tool holder, mixer          | M14                |
| No-load speed, 1st gear     | 0 - 780 rpm        |
| Clamping collar diameter    | 53 mm              |
| Cable length                | 4,0 m              |
| Dimensions WxLxH            | 405 x 215 x 340 mm |
| Weight                      | 4,5 kg             |

## Standard equipment

1 Open-ended wrench SW 19 (439967)  
1 Open-ended wrench SW 22 (439975)  
1 Helix paddle HP2 (534027)