

BRE 16-3 125

Pipe belt sander

Order no. 535341

GTIN 4030293291812



- + Microprocessor control: speed selection, tachogenerator constant speed control, soft start, restart protection after power failure, overload protection and temperature monitoring
- + Completely cast electronic components prevents damage due to metal dust. The 3-fold winding protection reduces motor wear, increases service life
- + Sanding belt replacement: quick and tool-free
- + Sanding belt dimension: 760 x 40 mm
- + High-quality, spring-mounted sanding arm: light alloy with 2 deflection rollers. For optimum wrap-round on pipes, up to max. 270° / Ø 125 mm
- + Spindle lock



Soft Start



Constant Drive Control



Temperature Monitoring



Overload Protection



Restart Protection

Technical data

Power consumption	1600 W
Power output	950 W
Voltage	230 V
Frequency	50/60 Hz
Belt speed	4.4 - 12.6 m/sec
No-load speed	1400 - 3900 rpm
Belt length	760 mm
Belt width	40 mm
Suitable for max. pipe diameter	125 mm
Cable length	4,0 m
Dimensions WxLxH	495 x 185 x 350 mm
Weight	3,4 kg

Standard equipment

1 Side handgrip (462985)

www.flex-tools.com

this is proformance **FLEX**