

CS 62 18.0-EC

Cordless circular saw with pendulum hood 18,0 V

Order no. 417939

GTIN 4030293180437

- + Ideal for traditional applications in dry construction and refurbishing, e.g. for making saw cuts through plasterboard, concrete fibre boards, wood materials, such as formwork panels and chipboard or OSB boards
- + Brushless motor with greater efficiency and a longer service life
- + 18 V EC motor with overload protection and temperature monitoring
- + Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- + Angle scale from 0 ° to 50 °. With preset angles of 22.5°/ 45°, and 50°. Easy to read, precision adjustment via non-slip clamping elements
- + Dual clamped swivel element prevents the saw blade from jamming when making mitre cuts and therefore the risk of recoil
- + Swivel range from 0° to 50° for undercuts as well as scoring function for perfect visible edges
- + Intuitive clamp lever for cutting depth adjustment, cutting depth is easy to read off
- + Connector for external dust extraction Ø 27 mm or step adapter
- + Woodshaving collection bag for low-dust operation, simple to empty, tool-free attachment by means of bayonet connection
- + In accordance with the latest regulations without splitting wedge for plunge cuts and without time-consuming removal of splitting wedge
- + Spindle lock: for quick replacement of blades
- + LED battery capacity display
- + FLEX battery system: suitable for all FLEX 18 V battery packs. Delivery does not include battery and charger



Technical data

| | |
|--------------------------------|---------------------|
| Battery voltage | 18.0 V |
| Battery capacity | 2.5 / 5.0 / 8.0 Ah |
| Max. no-load speed | 5000 rpm |
| Cutting depth | 0-62 mm |
| Cutting depth, mitre cut (45°) | 0-38 mm |
| Saw blade diameter | 165 mm |
| Saw blade hole | 20 mm |
| Pivoting range | 0-50° |
| Angle preset | 0 / 22,5 / 45 / 50° |
| Dimensions WxLxH | 380 x 150 x 200 mm |
| Weight without battery pack | 3.1 kg |

Standard equipment

- 1 Standard circular saw blade with alternating teeth (456012)
- 1 Carrying case L-BOXX® (414107)
- 1 Case insert (459380)
- 1 Dust bag