

CS 68 18-EC

Cordless circular saw with pendulum hood 18 V

Order no. 532637

GTIN 4030293264779



- + Ideal for traditional applications in dry construction and refurbishing, e.g. for making saw cuts through plasterboard, concrete fibre boards, wood materials, such as formwork panels and chipboard or OSB boards
- + Angle scale from 0 ° to 56 °. With preset angles of 22.5°/ 45°, and 56°. Easy to read, precision adjustment via long clamping lever
- + High-quality magnesium die-castings for protective cover and base plates
- + Guide rails for straight, splinter-free and powerful cuts. The guide rail slots are located directly in the base plate. Compatible with FLEX and other systems
- + Brushless motor with greater efficiency and a longer service life
- + 18 V EC motor with overload protection and temperature monitoring
- + Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- + Motor brake stops the saw blade in 2 seconds
- + Integrated LED lamp for optimum illumination of the work area.
- + Spindle lock: for quick replacement of blades
- + With metal bracket for flexible attachment
- + Connector for external dust extraction Ø 27, 36 mm
- + Woodshaving collection bag for low-dust operation, simple to empty
- + LED battery capacity display
- + FLEX battery system: suitable for all FLEX 18 V battery packs. Delivery does not include battery and charger



Technical data

Battery voltage	18 V
Battery capacity	2.5 / 5.0 / 8.0 Ah
Max. no-load speed	5800 rpm
Cutting depth	0-68 mm
Cutting depth, mitre cut (45°)	0-50 mm
Saw blade diameter	190 mm
Saw blade hole	20 mm
Pivoting range	0.56°
Angle preset	0 / 22,5 / 45°
Dimensions WxLxH	352 x 200 x 273 mm
Weight without battery pack	4.3 kg

Standard equipment

- 1 Standard circular saw blade with alternating teeth (532703)
- 1 Parallel stop
- 1 Dust bag
- 1 Carrying case L-BOXX® (414107)
- 1 Case insert (533167)