## this is proformance



## ALC3/360-G/R 12

360° cross-line laser with receiver mode Order no. 532277 GTIN 4030293261174



- The lines are at 90° to each other and allow for quick alignment and assem-
- Plumb function, the vertical cross points are automatically the plumb point
- Specially coated glasses ensure clean and high-precision laser lines.
- The green line is easily visible, even in bad lighting conditions
- 🛟 Extended range of 100 m, with receiver up to 120 m working range
- Self-levelling
- Optical warning signal when self-levelling range exceeded
- On/Off switch for self levelling function, so that the laser beam can be adjusted manually
- Brightness control across 3 levels, selection according to ambient brightness or battery status. Level 1 is also the receiver mode
- Dust- and splash-proof
- 1/4" and 5/8" thread for tripod
- With vertical and horizontal levelling the ALC is best suitable for interior finishing, for setting out doors, windows, walls, cupboards, and mirror tiles etc. And for many different setting out jobs on the building site
- FLEX battery system: suitable for all FLEX 12 V battery packs. Delivery does not include battery and charger







## **Technical data**

iecillicai data	
Number of lines, horizontal	1 Cont.
Number of lines, vertical	2 Cont.
Visible range, horizontal lines	360°
Visible range, vertical lines	360°
Laser class	2
Max. operating range	100 m
Max. operating range with receiver	120 m
Precision	± 0,3 mm
Self-levelling range	4°
Operating time	12 h
Temperature range	-10 - +40 °C
Protection class	IP54
Power supply	Battery system
Battery voltage	12 V
Battery capacity	2,5 / 5,0 Ah
Dimensions WxLxH	152 x 88 x 130 mm
Weight without battery pack	0,8 kg

## Standard equipment

- 1 Carrying case L-BOXX® (414085)
- 1 Laser target plate and goggles, green (500763) 1 Laser universal bracket (500747)