

MXE 1000 + HP2 120

1010 watt 1-speed mixer with accelerator trigger switch

Order no. 495883

GTIN 4030293224445

- + Large, rugged single-speed gear unit with optimum gear ratio for high torque
- + Full-wave electronic control: with soft start, temperature monitoring, overload protection and accelerator switch - for a controlled run-up to the optimum mixing speed. Sustained power in all speed ranges
- + On/off switch with lock and protection at power interruption. Ideal for stationary operation in a mixing station
- + The flexible rubber sleeve over the on/off switch prevents the ingress of dirt. No malfunctions caused by jammed switches
- + Ergonomic handles on the drive unit: low weight, fatigue-free arm posture and upright body posture allow comfortable, ergonomic operation
- + Four corner guards with rubber buffer provide secure storage during transportation and offer protection against shocks and impacts at the building site
- + Protective cap above the motor housing guides the cooling air flow and prevents the ingress of splashing water
- + For mixed applications up to 40 kg
- + Proven standard mixer is ideal for users operating mainly in the low speed range
- + With mixing paddle WR2 for mixture: pasty to tough. Tile adhesive, grout, filler compound, adhesive, finished plaster, adhesive mortar, ...



Technical data

Power consumption	1010 W
Power output	550 W
Voltage	230 V
Frequency	50/60 Hz
Max. mixing basket diameter	120 mm
Tool holder, mixer	M14
No-load speed, 1st gear	0 - 780 rpm
Clamping collar diameter	53 mm
Cable length	4.0 m
Dimensions WxLxH	405 x 215 x 340 mm
Weight	4.5 kg

Standard equipment

- 1 Open-ended wrench SW 19 (439967)
- 1 Open-ended wrench SW 22 (439975)
- 1 Helix paddle HP2 (534027)