

# MXE 1202 + HP2 140

**1200 watt 2-speed mixer with 3-level speed switch**

**Order no. 495921**

**GTIN 4030293224483**

- + Large, rugged 2-gear unit with optimum ratios for powerful torque and correct speed for different materials
- + Full-wave electronic control: with soft start, temperature monitoring, overload protection and accelerator switch - for a controlled run-up to the optimum mixing speed. Sustained power in all speed ranges
- + Comfortable 3-level switch can be reached from the grip position without interrupting work, protected by a rubber sleeve. Level 1: cleaning, level 2: stirring up, level 3: mixing
- + On/off switch with lock and protection at power interruption. Ideal for stationary operation in a mixing station
- + The flexible rubber sleeve over the on/off switch prevents the ingress of dirt. No malfunctions caused by jammed switches
- + Ergonomic handles on the drive unit: low weight, fatigue-free arm posture and upright body posture allow comfortable, ergonomic operation
- + Four corner guards with rubber buffer provide secure storage during transportation and offer protection against shocks and impacts at the building site
- + Protective cap above the motor housing guides the cooling air flow and prevents the ingress of splashing water
- + Spindle lock with start-up protection. Simplifies exchange of the mixing paddle
- + For mixed applications up to 60 kg
- + With mixing paddle WR2 for mixture: pasty to tough. Tile adhesive, grout, filler compound, adhesive, finished plaster, adhesive mortar, ...



Throttle switch



Soft Start



Constant Drive Control



Temperature Monitoring



Overload Protection



Restart Protection



Spindle-lock

## Technical data

|                             |                     |
|-----------------------------|---------------------|
| Power consumption           | 1200 W              |
| Power output                | 710 W               |
| Voltage                     | 230 V               |
| Frequency                   | 50/60 Hz            |
| Max. mixing basket diameter | 140 mm              |
| Tool holder, mixer          | M14                 |
| No-load speed, 1st gear     | 0 - 210/325/530 rpm |
| No-load speed, 2nd gear     | 0 - 320/490/780 rpm |
| Clamping collar diameter    | 53 mm               |
| Cable length                | 4.0 m               |
| Dimensions WxLxH            | 405 x 215 x 340 mm  |
| Weight                      | 4.8 kg              |

## Standard equipment

- 1 Open-ended wrench SW 22 (439975)
- 1 Helix paddle HP2 (534028)