

ODE 2-100 EC Set

Compact delta sander with speed control

Order no. 468908

GTIN 4030293209763

- + Lightweight, compact one-handed delta sander, very ergonomic and low-vibration thanks to special balancing for fatigue-free and joint-friendly work
- + Brushless motor with greater efficiency and a longer service life
- + Electronics: Speed preselection with 4 settings, constant speed control by means of tachogenerator, soft start, restart protection
- + Sanding speed suitable for the material thanks to electronic speed adjustment
- + Hook & loop backing pad with 10-hole system for optimum extraction, suitable for all standard abrasives
- + E-signal switch for simple, safe operation with quick-stop function prevents trailing of the backing pad
- + Equipped with disc brake, as a result no unwanted sanding marks are produced on the workpiece and expensive corrective finishing is not required
- + Effective dust extraction thanks to integrated extractor for dust-free working with filter cartridge
- + External dust extraction Ø 27 mm, antistatic suction hose SH 27x3,5m AS (445.045) can be connected
- + Impact-resistant filter cartridge with exchangeable PES filter allows simple dust disposal or cleaning of the filter as well as maximum service life
- + Especially suitable for overhead work



Technical data

| | |
|-------------------------------------|-------------------|
| Power consumption | 260 W |
| Voltage | 230 V |
| Frequency | 50/60 Hz |
| Stroke | 2 mm |
| No-load speed | 8000 - 12000 rpm |
| Orbit rate, no load | 16000 - 24000 rpm |
| Backing pad width | 100 mm |
| Backing pad length | 150 mm |
| Diameter dust extraction connection | Ø 27 |
| Cable length | 4.0 m |
| Dimensions WxLxH | 156 x 90 x 121 mm |
| Weight | 1.2 kg |

Standard equipment

- 1 Hook-and-loop backing pad Delta (468991)
- 1 PES microfilter cartridge (486833)
- 1 Case insert (516066)
- 1 Carrying case L-BOXX® (414093)