

GCE 6-EC Kit


Handy-Giraffe® wall and ceiling sander with interchangeable head system

Order no. 504114

GTIN 4030293230118



- + Ideally suited for sanding plaster boards, solid styropor insulation slabs, preparation for painting
- + Lightweight and easy-to-use on small surfaces, tight spaces
- + Completely cast electronic components prevents damage due to metal dust. The 3-fold winding protection reduces motor wear, increases service life
- + Fitted with innovative interchangeable head system. Sanding heads are attached and removed with a click
- + Grip hood for easy handling and precise working
- + Brushless motor with greater efficiency and a longer service life
- + Electronic control: stepless speed selection, constant speed, overload protection and temperature monitoring
- + Effective dust extraction from between the brush ring and the sanding pad prevents clogging of the abrasive and promotes a dust-free working environment
- + Defined hose guidance and effective dust extraction due to large hose cross-section. The suction hose is directly attached to the tool by the FLEX clip-system
- + Machine without sanding head as an addition for the Giraffe® GE 7



Technical data

Power consumption	600 W
Power output	400 W
Voltage	230 V
Frequency	50/60 Hz
Backing pad diameter	225 mm
No-load speed	1100 - 1650 rpm
Orbit rate, no load MH-T	3800-5700 1 rpm
Orbit rate, no load MH-X	3100-4600 1 rpm
Tool holder, wall and ceiling sander	hook and loop
Cable length	4,0 m
Length	360 mm
Dimensions WxLxH	360 x 110 x 150 mm
Weight	1,2 kg

Standard equipment

- 1 Carrying case L-BOXX® (414107)
- 1 Case insert (500798)