this is proformance



VCE 22 M MC V

Safety vacuum cleaner with manual filter cleaning system, 20 l, class M
Order no. 530920
GTIN 4030293247604

- Handy and compact vacuum cleaner, easy to use and easy to transport
- The high-performance turbine ensures both a high suction capacity and a high vacuum. The outcome is an excellent extraction result
- By actuating manual filter cleaning, dust deposited in the filter element is removed by a targeted blast of air
- Level monitor, no malfunctions when drawing in liquids thanks to installed float valve
- With appliance socket and electronic automatic switch on/off
- Soft start stops any voltage peaks at the start and the run-on feature (5 sec. overrun) empties any remaining dust in the vacuum hose
- With accessories magazine for suction nozzles and suction tubes on the back
- Equipped with large wheels and two swivel guide rollers
- Features a filter bag made of highly tear-proof fleece for optimum filling. The extracted dust can be disposed of without difficulty
- Selector switch suction diameter of 32 mm or 21 mm to adjust the optimum flow rate
- The flow rate control via the rotary switch minimises possible vacuums on the surface during intermediate and finish sanding
- Dust-protected antistatic finish prevents electric charging of the suction hose
- Class M safety vacuum cleaner, suitable for all dusts with OEL values ≥ 0.1 mg/m³. Specifically for mineral and timber dusts (also beech and oak)
- Flow sensor technology monitors the flow rate and emits an audible signal to indicate any drop below the statutory minimum value of ≤ 20m/s













Technical data

| Power consumption | 1200 W |
|----------------------------------|------------|
| Voltage | 230 V |
| Frequency | 50/60 Hz |
| Vacuum cleaner flow rate | 3700 l/min |
| Max. vacuum | 24500 Pa |
| Tank volume | 20 L |
| Equipment socket | Yes |
| Automatic switch-on, power tools | Yes |
| Suction power control | mechanical |
| Hose length | 3.5 |
| Number of suction motors | 1 Cont. |
| Cable length | 7.5 m |
| Weight | 9.5 kg |
| | |

Standard equipment

1 Antistatic suction hose (445045)