this is proformance



DCG L 26-6 230 Set

Diamond cutting system, 230 mm Order no. 494631 GTIN 4030293224148

- Ready to go straight away, angle grinder with already installed extraction hood in the case. Diamantjet - Standard 230 mm diamond cutting wheel for concrete included
- Powerful angle grinder L 26-6 230 with soft start, restart protection after power failure, overload protection, CDC-electronic feedback control, anti-kickback function
- G Fully encapsulated extraction hood for efficient dust extraction
- Direct connection via Flex Clip system
- Extremely sturdy construction. The stabiliser element prevents distortion caused by the side weight of the angle grinder.
- Base plate with rollers for easy feed. Can be used with or without a guide rail
- Depth stop with scale for cutting depth adjustments and individual cuts (plunge cuts) with or without guide rail (max. 55 mm with, 60 mm without guide rail)
- Side handle can be fitted on either the left or right
- Case including lid compartment for small parts, storage space for diamond cutting wheel, side handle and 800 mm guide rail.





Technical data

Power consumption	2600 W
Power output	1800 W
Voltage	230 V
Frequency	50/60 Hz
Max. disc diameter	230 mm
No-load speed	
Tool holder, angle grinder	M14
Cable length	4.0 m
Dimensions WxLxH	610 x 195 x 290 mm
Weight	9.18 kg
Cutting depth	60 mm

Standard equipment

- 1 Extraction hood cutting for large angle grinder, 230 mm (471895)
- 1 Diamantjet diamond cutting disc, universal (500720)

3 Rubber strip (494593)

- 1 Distance ring (494615) 1 SoftVib side handle (325384)
- 1 Clamping nut M 14 (100080)
- 1 Hexagon socket wrench, SW 6 (104167)
- 1 Face pin spanner (100110)
- 1 Carrying case (499579)
- 1 Clamping flange (335282)