
this is proformance



ODE 2-100 18-EC/2.5 Se

18 V cordless delta sander with speed control Order no. 532089
GTIN 4030293259294



- Ergonomically designed, handy grip cover with soft grip insert ensures a secure grip and good guidance
- Sanding speed suitable for the material thanks to electronic speed adjustment
- E-signal switch for simple, safe operation with quick-stop function prevents trailing of the backing pad
- Hook & loop backing pad with 10-hole system for optimum extraction, suitable for all standard abrasives
- External dust extraction Ø 27 mm, antistatic suction hose SH 27x3,5m AS (445.045) can be connected
- 1 Integrated dust extraction with dust filter bag
- Brushless motor with greater efficiency and a longer service life
- Electronics: Speed preselection with 4 settings
- Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- LED battery capacity display
- ♣ FLEX battery system: suitable for FLEX 18,0 V/5,0/2,5 Ah battery packs











Technical data

| Battery voltage | 18 V |
|-------------------------------------|--------------------|
| Battery capacity | 2,5 / 5,0 Ah |
| Stroke | 2 mm |
| No-load speed | 6000 - 10000 rpm |
| Orbit rate, no load | 12000 - 20000 rpm |
| Backing pad width | 100 mm |
| Backing pad length | 150 mm |
| Diameter dust extraction connection | Ø 27 |
| Dimensions WxLxH | 228 x 100 x 140 mm |
| Weight without battery pack | 1,0 kg |
| | |

Standard equipment

- 1 Adapter, short (532094)
- 1 Adapter, long (532095)
- 2 Li-lon rechargeable battery pack 18 V (532732)
- 1 Carrying case L-BOXX® (414093)
- 1 Case insert (532882)
- 1 Rapid charger 12/18 V (532280)