

ALC 2/1-G/R

Self-levelling crossline laser with receiver mode

Order no. 509833

GTIN 4030293232945

- + With an individually switchable horizontal and vertical laser line
- + Specially coated glasses ensure clean and high-precision laser lines.
- + Green laser diode
- + The green line is easily visible, even in bad lighting conditions
- + Extends the range from 50 metres up to 70 metres with receiver
- + Self-levelling
- + Optical warning signal when self-levelling range exceeded
- + Self-levelling which can be switched off
- + Simple operation
- + Integrated Li-polymer rechargeable battery
- + Transportation lock
- + 1/4" thread for tripod



Technical data

Number of lines, horizontal	1 Cont.
Number of lines, vertical	1 Cont.
Visible range, horizontal lines	110°
Visible range, vertical lines	110°
Laser class	2
Max. operating range	50 m
Max. operating range with receiver	70 m
Precision	± 0,3 mm
Self-levelling range	4°
Operating time	10 h
Temperature range	-5 - +50 °C
Protection class	IP54
Power supply	Integrated battery
Dimensions WxLxH	57 x 96 x 96.5 mm
Weight	0.36 kg

Standard equipment

- 1 Laser wall bracket (428167)
- 1 USB-cable
- 1 USB-charger
- 1 Carrying bag