this is proformance



L 26-6 230

2600 watt angle grinder, 230 mm Order no. 531045 GTIN 4030293248854



- O Microprocessor control with soft start, restart protection after power failure, overload protection, CDC-electronic feedback control
- Anti-Kickback this shuts down the motor on the disc being blocked
- Bear shaft handle with soft padding for secure grip. The grip area turns 90° to the right and left for an optimum working position
- Bobust motor housing and gearbox housing. Stable and robust steel gearbox as well as a spindle bearing protected by a metal cap also increase reliability and durability
- Highly efficient and resilient motor for more power output
- An additional vibration damping ring between the motor housing and rear handle reduces the vibrations.
- SoftVib handgrip for reduced vibration can be mounted in three positions.
- Spindle lock
- Removable covering cap for easy change of carbon brushes
- Tool-free adjustment of safety guard
- Cutting guard (389.625) or cover for cutting guard (446.068), as an optional accessory



Technical data

Power consumption	2600 W
Power output	1800 W
Voltage	230 V
Frequency	50/60 Hz
Max. disc diameter	230 mm
No-load speed	6500 rpm
Tool holder, angle grinder	M14
Cable length	4.0 m
Dimensions WxLxH	500 x 106 x 145 mm
Weight	6.35 kg

Standard equipment

- 1 Sanding guard (442828) 1 SoftVib side handle (325384)
- 1 Quick-clamp nut M 14 (530726)

1 Hexagon socket wrench, SW 6 (104167)

1 Clamping flange (335282)

1 Sanding/cutting guard (534105)