




- + 15 mm orbit for high efficiency
- + Free-spinning drive for hologram-free finishing
- + Low heat generation on the surface makes it ideal for temperature-sensitive paints
- + Powerful 700 watt motor with highly-efficient ventilator for optimum cooling
- + Optimised air flow for optimum cooling of motor and gear. No annoying exhaust air for the user
- + Continuous speed control trigger: for a gentle start and a lock-on for continuous operation
- + VR microprocessor control: with tachogenerator constant speed control, soft start, continuous speed control trigger, restart protection after power failure, overload protection, temperature monitoring and speed selection
- + Flat gear head reduces distance to the surface. The machine can therefore be operated safely in any position.
- + Counterweight for smoother operation
- + Cushioned special hook and loop pad for polishing.
- + Grip hood: ergonomically shaped with SoftGrip. The machine can be controlled with precision and is always comfortable yet secure to hold.
- + With rubberised resting bar for safe setting down
- + 4 metres PUR H05-BQF cable: wear-resistant, flexible and highly resistant to cuts and abrasions



Technical data

Power consumption	710 W
Power output	420 W
Voltage	230 V
Frequency	50/60 Hz
Max. polishing disc size	160 mm
Max. support plate size	150 mm
Polishing stroke	15 mm
No-load speed	1500 - 4500 rpm
Orbit rate, no load	3000 - 9000 rpm
Cable length	4.0 m
Dimensions WxLxH	370 x 40 x 140 mm
Weight	2.4 kg

Standard equipment

- 1 Special hook-and-loop pad, cushioned (487953)
- 1 Special hook-and-loop pad, cushioned (487988)