this is proformance



ALC 2/1-G/R

Self-levelling crossline laser with receiver mode Order no. 509833 GTIN 4030293232945

- With an individually switchable horizontal and vertical laser line
- Specially coated glasses ensure clean and high-precision laser lines.
- Green laser diode
- The green line is easily visible, even in bad lighting conditions
- 🛟 Extends the range from 50 metres up to 70 metres with receiver
- Self-levelling
- Optical warning signal when self-levelling range exceeded
- Self-levelling which can be switched off
- Simple operation
- 1 Integrated Li-polymer rechargeable battery
- Transportation lock
- 1/4" thread for tripod







Technical data

Number of lines, horizontal	1 Cont.
Number of lines, vertical	1 Cont.
Visible range, horizontal lines	110°
Visible range, vertical lines	110°
Laser class	2
Max. operating range	50 m
Max. operating range with receiver	70 m
Precision	± 0,3 mm
Self-levelling range	4°
Operating time	10 h
Temperature range	-5 - +50 °C
Protection class	IP54
Power supply	Integrated battery
Dimensions WxLxH	57 x 96 x 96.5 mm
Weight	0.36 kg

Standard equipment

- 1 Laser wall bracket (428167) 1 USB-cable
- 1 USB-charger
- 1 Carrying bag