

PXCE 18-EC Set

18 V cordless polisher, rotary, random orbital with free-running and forced rotation

Order no. 535578

GTIN 4030293294189

- + The ideal cordless polisher for every vehicle refurbisher and painter and for the spot repair sector
- + More flexible and easier than ever before, from sanding to hologram-free finishing with a single unit
- + Intuitive touch panel for speed adjustment. Lock function prevents accidental operation - can be activated while wearing gloves
- + Innovative quick-change system for exchanging all three rotary and random orbital free-running/forced rotation drive types without using tools
- + For rotary work - disc sizes 30, 50 and 75 mm can be used
- + Suitable for random orbital free-running work with 3/6/12 mm stroke and for random orbital forced-rotation work with 6 mm stroke. Disc sizes 30, 50 and 75 mm can be used
- + Newly-developed motor design for maximum noise and vibration reduction
- + Perfect ergonomics and flexible grip options because of its ideally placed softgrip surfaces
- + Continuous speed control trigger: for a gentle start and a lock-on for continuous operation
- + Integrated three-level LED lamp with a light temperature of 2,500 to 6,500 K, enabling accurate adjustment to the job at hand
- + Brushless motor with greater efficiency and a longer service life
- + Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- + LED battery capacity display
- + FLEX battery system: suitable for all FLEX 18 V battery packs



Technical data

Battery voltage	18 V
Max. support plate size	75 mm
Polishing stroke	3 / 6 / 12 mm
No-load speed	1000 - 6000 rpm
Orbit rate, no load	2000 - 12000 rpm
Number of supplied batteries	2 Cont.
With charger	Yes
Dimensions WxLxH	282 x 79 x 86 mm
Weight without battery pack	0.9 kg
Sound pressure level	67 dB(A)
Vibration	2.8 m/s ²

Standard equipment

- 1 Adapter eccentrically free-running, 3 mm stroke (537154)
- 1 Adapter eccentrically free-running, 6 mm stroke (537155)
- 1 Free spin random orbital adapter, 12 mm stroke (537156)
- 1 Eccentric, forced-rotation adapter (537157)
- 1 Rotary adapter (537152)
- 1 Extension for DT-XC 6 PXCE (537153)
- 1 Special adhesive pad, cushioned (537161)
- 1 Special hook-and-loop pad, cushioned (537158)
- 1 Special hook-and-loop pad, cushioned (537159)
- 1 Special hook-and-loop pad, cushioned (537160)
- 1 Rapid charger 12/18 V (535296)
- 2 Li-Ion rechargeable battery pack 18 V (535440)

www.flex-tools.com

this is proformance **FLEX**