www.flex-tools.com

this is proformance FLEX

BRE 14-3 125 Set

Pipe belt sander TRINOXFLEX Set

Order no. 433446

GTIN 4030293187191



- Microprocessor control: speed selection, tachogenerator constant speed control, soft start, restart protection after power failure, overload protection and temperature monitoring
- Unique tool attachment with quick-action coupling for tool-free changing of the system attachments for burnishing and pipe belt sanding
- Completely cast electronic components prevents damage due to metal dust. The 3-fold winding protection reduces motor wear, increases service life
- Sanding belt replacement: quick and tool-free
- Sanding belt dimension: 760 x 40 mm
- High-quality, spring-mounted sanding arm: light alloy with 2 deflection rollers. For optimum wrap-round on pipes, up to max. 270°
- Spindle lock



Technical data

Power consumption	1400 W
Power output	880 W
Voltage	230 V
Frequency	50/60 Hz
Belt speed	3.5 - 10 m/sec
No-load speed	1000 - 3500 rpm
Belt length	760 mm
Belt width	40 mm
Suitable for max. pipe diameter	125 mm
Cable length	4.0 m
Dimensions WxLxH	520 x 160 x 220 mm
Weight	3.6 kg

Standard equipment

1 Sanding attachment, pipe belt (433470)
1 Superfinishing band (326917)
1 Superfinishing band (326933)
1 Sanding belt MESHFLEX (326879)
1 Sanding belt MESHFLEX (326852)
5 Sanding belt CORUFLEX (326739)
5 Sanding belt CORUFLEX (326755)
5 Sanding belt CORUFLEX (434914)
1 Carrying case L-BOXX® (414093)
1 Case insert (433918)