www.flex-tools.com

this is proformance FLEX

FBE 8-4 140


Belt file TRINOXFLEX

Order no. 453455

GTIN 4030293201071



- Microprocessor control: speed selection, tachogenerator constant speed control, soft start, restart protection after power failure, overload protection and temperature monitoring
- VE electronic control: for infinitely adjustable belt speed
- Unique tool attachment with quick-action coupling for tool-free changing of the system attachments for burnishing, pipe belt sanding, filing
- Completely cast electronic components prevents damage due to metal dust. The 3-fold winding protection reduces motor wear, increases service life
- Sanding head: rotates through 140°. For use with sanding arms in 9 mm or 30 mm
- Sanding arm adjustable for 520 mm and 533 mm belt lengths
- Processing length sanding arm up to approx. 12 cm
- Sanding belt replacement: quick and tool-free



Technical data

Power consumption	800 W
Power output	425 W
Voltage	230 V
Frequency	50/60 Hz
No-load speed	1400 - 4000 rpm
Belt speed	3 - 8 m/sec
Belt length	533 mm
Belt width	4-30 mm
Cable length	4.0 m
Dimensions WxLxH	320 x 210 x 195 mm
Weight	2.6 kg

Standard equipment

1 Sanding attachment, belt file (459593)
2 Sanding belt ZIRCOFLEX (303615)
2 Sanding belt ZIRCOFLEX (303623)
2 Sanding belt ZIRCOFLEX (257105)
2 Sanding belt ZIRCOFLEX (257102)
2 Sanding belt ZIRCOFLEX (255328)
2 Sanding belt ZIRCOFLEX (255329)
1 Sanding belt MESHFLEX (318663)
1 Sanding belt MESHFLEX (318647)
1 Side handle, red (194034)
1 Hexagon socket wrench, SW 5 (115460)
1 Carrying case L-BOXX® (414085)
1 Case insert (457337)