www.flex-tools.com

this is proformance FLEX

BRE 8-4 INOX Set

Pipe belt sander and belt file TRINOXFLEX Set

Order no. 453463

GTIN 4030293201088



- Microprocessor control: speed selection, tachogenerator constant speed control, soft start, restart protection after power failure, overload protection and temperature monitoring
- Unique tool attachment with quick-action coupling for tool-free changing of the system attachments for burnishing, pipe belt sanding, filing
- Completely cast electronic components prevents damage due to metal dust. The 3-fold winding protection reduces motor wear, increases service life
- Sanding belt replacement: quick and tool-free
- Sanding belt dimension: 533 x 4 - 30 mm
- High-quality, spring-mounted sanding arm: light alloy with 2 deflection rollers. For optimum wrap-round on pipes, up to max. 270°
- Spindle lock



Technical data

Power consumption	800 W
Power output	425 W
Voltage	230 V
Frequency	50/60 Hz
Belt speed	3 - 8 m/sec
No-load speed	1400 - 4000 rpm
Belt length	533 mm
Belt width	4/9/30 mm
Suitable for max. pipe diameter	50 mm
Cable length	4.0 m
Dimensions WxLxH	320 x 210 x 195 mm
Weight	2.6 kg

Standard equipment

1 Sanding attachment, pipe belt (459585)
1 Sanding attachment, belt file (459593)
1 Interchangeable roller set (459607)
2 Sanding belt ZIRCOFLEX (303615)
2 Sanding belt ZIRCOFLEX (303623)
2 Sanding belt ZIRCOFLEX (257105)
2 Sanding belt ZIRCOFLEX (257102)
2 Sanding belt ZIRCOFLEX (255328)
2 Sanding belt ZIRCOFLEX (255329)
1 Sanding belt MESHFLEX (318663)
1 Sanding belt MESHFLEX (318647)
1 Side handle, red (194034)
1 Hexagon socket wrench (102229)
1 Hexagon socket wrench, SW 5 (115460)
1 Hexagon socket wrench, SW 6 (104167)
1 Carrying case L-BOXX® (414085)
1 Case insert (457337)